

# SAFETY DATA SHEET

Date Printed: 05/05/2024

Date Revised: 01/15/2022

## SECTION 1. IDENTIFICATION

**Product Identifier:** (4N) 99.99% Thallium(III) Nitrate Trihydrate

**Product Code:** TL-NAT-04-C.3HYD

**CAS Number:** 13453-38-8

**Relevant identified uses of the substance:** Scientific research and development

Supplier details:

American Elements  
10884 Weyburn Ave.  
Los Angeles, CA 90024  
Tel: +1 310-208-0551  
Fax: +1 310-208-0351  
Emergency telephone number:  
+1 800-424-9300

## SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Oxidizing solids (Category 3), H272

Acute toxicity, Oral (Category 2), H300

Acute toxicity, Inhalation (Category 2), H330

Acute aquatic toxicity (Category 2), H401

Chronic aquatic toxicity (Category 2), H411

2.2 GHS Label elements, including precautionary statements



Pictogram

Signal word Danger

Hazard statement(s)

H272 May intensify fire; oxidiser.

H300 + H330 Fatal if swallowed or if inhaled

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat.

P220 Keep/Store away from clothing/ combustible materials.  
P221 Take any precaution to avoid mixing with combustibles.  
P260 Do not breathe dust/ fume/ gas/ mist/ Vapors/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.  
P284 Wear respiratory protection.  
P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.  
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.  
P391 Collect spillage.  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P501 Dispose of contents/ container to an approved waste disposal plant.  
2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

---

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

### **3.1 Substances**

Synonyms : TTN

Formula :  $\text{N}_3\text{O}_9\text{TI} \cdot 3\text{H}_2\text{O}$

Molecular weight : 444.44 g/mol

CAS-No. : 13453-38-8

EC-No. : 237-325-4

Index-No. : 081-002-00-9

Hazardous components

Component Classification Concentration

Thallium trinitrate trihydrate

Ox. Sol. 3; Acute Tox. 2;

Aquatic Acute 2; Aquatic

Chronic 2; H272, H300 +

H330, H411

$\leq 100\%$

---

## **SECTION 4. FIRST AID MEASURES**

### **4.1 Description of first aid measures**

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## **SECTION 5. FIREFIGHTING MEASURES**

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Nitrogen oxides (NO<sub>x</sub>), thallium oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

---

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing Vapors, mist or gas. Ensure adequate ventilation.

Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment

must be avoided.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing

and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed

containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

---

## **SECTION 7. HANDLING AND STORAGE**

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result

in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration

before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Keep away from heat and sources of ignition.  
For precautions see section 2.2.  
7.2 Conditions for safe storage, including any incompatibilities  
Keep container tightly closed in a dry and well-ventilated place.  
Hygroscopic.  
Storage class (TRGS 510): Oxidizing hazardous materials  
7.3 Specific end use(s)  
Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Components with workplace control parameters

Component CAS-No. Value Control parameters

Basis

Thallium trinitrate

trihydrate

13453-38-8 TWA 0.100000

mg/m<sup>3</sup>

USA. Occupational Exposure Limits

(OSHA) - Table Z-1 Limits for Air

Contaminants

Remarks Skin contact does contribute to exposure.

TWA 0.020000

mg/m<sup>3</sup>

USA. ACGIH Threshold Limit Values

(TLV)

Peripheral neuropathy

Gastrointestinal damage

Danger of cutaneous absorption

varies

### 8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate

government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without

touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after

use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test

method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the

supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It

should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to

the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type

N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the

sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and

approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

a) Appearance Form: crystalline

Colour: colourless

b) Odor No data available

c) Odor Threshold No data available

d) pH No data available

e) Melting point/freezing point

Melting point/range: 102 - 105 °C (216 - 221 °F) - lit.

f) Initial boiling point and boiling range

No data available

g) Flash point N/A

h) Evaporation rate No data available

i) Flammability (solid, gas) No data available

j) Upper/lower

flammability or

explosive limits

No data available

k) Vapor pressure No data available  
l) Vapor density No data available  
m) Relative density No data available  
n) Water solubility No data available  
o) Partition coefficient: noctanol/  
water  
No data available  
p) Auto-ignition  
temperature  
No data available  
q) Decomposition  
temperature  
No data available  
r) Viscosity No data available  
s) Explosive properties No data available  
t) Oxidizing properties The substance or mixture is classified as oxidizing with the category 3.  
9.2 Other safety information  
No data available

---

## **SECTION 10. STABILITY AND REACTIVITY**

10.1 Reactivity  
No data available  
10.2 Chemical stability  
Stable under recommended storage conditions.  
10.3 Possibility of hazardous reactions  
No data available  
10.4 Conditions to avoid  
No data available  
10.5 Incompatible materials  
Strong acids  
10.6 Hazardous decomposition products  
Other decomposition products - No data available  
In the event of fire: see section 5

---

## **SECTION 11. TOXICOLOGICAL INFORMATION**

11.1 Information on toxicological effects  
Acute toxicity  
No data available  
Dermal: No data available  
No data available  
Skin corrosion/irritation  
No data available  
Serious eye damage/eye irritation  
No data available  
Respiratory or skin sensitisation  
No data available  
Germ cell mutagenicity  
No data available  
Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity  
No data available  
No data available  
Specific target organ toxicity - single exposure  
No data available  
Specific target organ toxicity - repeated exposure  
No data available  
Aspiration hazard  
No data available  
Additional Information  
RTECS: Not available

The most characteristic symptom of thallium exposure is alopecia (loss of hair). Cutaneous effects may include dry, scaly skin and impairment of nail growth often resulting in the appearance of crescent-shaped strips across fingernails and toenails (Mees' line). Other symptoms in acute poisoning relate chiefly to the gastrointestinal tract, nervous system, skin, eyes, and cardiovascular system. Acute poisoning results in swelling of the feet and legs, arthralgia, vomiting, insomnia, hyperesthesia and paresthesia of the hands and feet, mental confusion, polyneuritis with severe pain in the legs and loins, partial paralysis of the legs, angina-like pains, nephritis, wasting and weakness, and lymphocytosis and eosinophilia. In chronic poisoning, central and peripheral nervous system abnormalities may persist including ataxia, tremor, incoordination, paralysis of extremities, endocrine disorders, memory loss, and psychoses may develop. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence  
Stomach - Irregularities - Based on Human Evidence

---

## **SECTION 12. ECOLOGICAL INFORMATION**

12.1 Toxicity  
No data available

12.2 Persistence and degradability  
No data available

12.3 Bioaccumulative potential  
No data available

12.4 Mobility in soil  
No data available

12.5 Results of PBT and vPvB assessment  
PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this

material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a

licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a

combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### DOT (US)

UN number: 2727 Class: 6.1 (5.1) Packing group: II

Proper shipping name: Thallium nitrate

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

### IMDG

UN number: 2727 Class: 6.1 (5.1) Packing group: II EMS-No: F-A, S-Q

Proper shipping name: THALLIUM NITRATE

Marine pollutant:yes Marine pollutant: yes

### IATA

UN number: 2727 Class: 6.1 (5.1) Packing group: II

Proper shipping name: Thallium nitrate

---

## SECTION 15. REGULATORY INFORMATION

### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Thallium trinitrate trihydrate

CAS-No.

13453-38-8

Revision Date

1987-01-01

### SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

### Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

### Pennsylvania Right To Know Components

Thallium trinitrate trihydrate



CAS-No.  
13453-38-8  
Revision Date  
1987-01-01  
New Jersey Right To Know Components  
Thallium trinitrate trihydrate

CAS-No.  
13453-38-8  
Revision Date  
1987-01-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

## 16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.