

SAFETY DATA SHEET

Date Printed: 05/19/2024

Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifier: Lithium-6 Fluoride

Product Code: LI6-F-01-P

CAS Number: 14885-65-5

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements
10884 Weyburn Ave.
Los Angeles, CA 90024
Tel: +1 310-208-0551
Fax: +1 310-208-0351
Emergency telephone number:
+1 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301

Reproductive toxicity (Category 2), H361

Effects on or via lactation, H362

2.2 GHS Label elements, including precautionary statements



Pictogram

Signal word Danger

Hazard statement(s)

H301 Toxic if swallowed.

H361 Suspected of damaging fertility or the unborn child.

H362 May cause harm to breast-fed children.

Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust or mist.
P263 Avoid contact during pregnancy/ while nursing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P281 Use personal protective equipment as required.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P321 Specific treatment (see supplemental first aid instructions on this label).
P330 Rinse mouth.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.
2.3 Hazards not otherwise classified (HNOC) or not covered by GHS
Strong hydrogen fluoride-releaser

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula : 6LiF

Molecular weight : 25.01 g/mol

CAS-No. : 14885-65-5

EC-No. : 238-958-9

Hazardous components

Component Classification Concentration

Lithium-6 fluoride

Acute Tox. 3; Repr. 2; Lact. ;

H301, H361, H362

<= 100 %

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Hydrofluoric

(HF) acid burns require immediate and specialized first aid and medical treatment. Symptoms may be delayed up to 24

hours depending on the concentration of HF. After decontamination with water, further damage can occur due to

penetration/absorption of the fluoride ion. Treatment should be directed toward binding the fluoride ion as well as the

effects of exposure. Skin exposures can be treated with a 2.5% calcium gluconate gel repeated until burning ceases.

More serious skin exposures may require subcutaneous calcium gluconate except for digital areas unless the physician

is experienced in this technique, due to the potential for tissue injury from increased pressure.

Absorption can readily

occur through the subungual areas and should be considered when undergoing decontamination.

Prevention of

absorption of the fluoride ion in cases of ingestion can be obtained by giving milk, chewable calcium carbonate tablets

or Milk of Magnesia to conscious victims. Conditions such as hypocalcemia, hypomagnesemia and

cardiac arrhythmias

should be monitored for, since they can occur after exposure.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician. First treatment with

calcium gluconate paste.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing Vapors, mist or gas. Ensure adequate ventilation.

Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols.
Provide appropriate exhaust ventilation at places where dust is formed.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Store under inert gas. hygroscopic

Do not store in glass

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component CAS-No. Value Control

parameters

Basis

Lithium-6 fluoride 14885-65-5 TWA 2.500000

mg/m³

USA. Occupational Exposure Limits

(OSHA) - Table Z-1 Limits for Air

Contaminants

Remarks CAS number varies with compound

TWA 2.500000

mg/m³

USA. Occupational Exposure Limits

(OSHA) - Table Z-2

Z37.28-1969

TWA 2.500000

mg/m³

USA. ACGIH Threshold Limit Values

(TLV)

Bone damage

Fluorosis

Substances for which there is a Biological Exposure Index or Indices

(see BEI® section)

Not classifiable as a human carcinogen

varies

TWA 2.500000

mg/m³

USA. ACGIH Threshold Limit Values

(TLV)

Bone damage

Fluorosis

Substances for which there is a Biological Exposure Index or Indices

(see BEI® section)

Not classifiable as a human carcinogen

varies

TWA 2.5 mg/m³ USA. Occupational Exposure Limits

(OSHA) - Table Z-1 Limits for Air

Contaminants

CAS number varies with compound

TWA 2.5 mg/m³ USA. ACGIH Threshold Limit Values

(TLV)

Bone damage

Fluorosis

Substances for which there is a Biological Exposure Index or Indices

(see BEI® section)

Not classifiable as a human carcinogen

varies

Biological occupational exposure limits

Component CAS-No. Parameters Value Biological

specimen

Basis

Lithium-6 fluoride 14885-65-5 Fluoride 3.0000

mg/g

In urine ACGIH - Biological

Exposure Indices

(BEI)

Remarks Prior to shift (16 hours after exposure ceases)

Fluoride 10.0000

mg/g

In urine ACGIH - Biological

Exposure Indices

(BEI)

End of shift (As soon as possible after exposure ceases)

Fluoride 2 mg/l Urine ACGIH - Biological

Exposure Indices

(BEI)

Prior to shift (16 hours after exposure ceases)

Fluoride 3 mg/l Urine ACGIH - Biological

Exposure Indices

(BEI)

End of shift (As soon as possible after exposure ceases)

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate

government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without

touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after

use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test

method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type

N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the

sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and

approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance Form: solid

b) Odor No data available

c) Odor Threshold No data available

d) pH No data available

e) Melting point/freezing point

Melting point/range: 842 °C (1,548 °F)

f) Initial boiling point and boiling range

No data available

g) Flash point N/A

h) Evaporation rate No data available

i) Flammability (solid, gas) No data available

j) Upper/lower

flammability or

explosive limits

No data available

k) Vapor pressure No data available

l) Vapor density No data available

m) Relative density No data available

n) Water solubility No data available

o) Partition coefficient: octanol/water

No data available

p) Auto-ignition
temperature
No data available
q) Decomposition
temperature
No data available
r) Viscosity No data available
s) Explosive properties No data available
t) Oxidizing properties No data available
9.2 Other safety information
No data available

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity
No data available
10.2 Chemical stability
Stable under recommended storage conditions.
10.3 Possibility of hazardous reactions
No data available
10.4 Conditions to avoid
Reacts dangerously with glass.
10.5 Incompatible materials
Strong oxidizing agents, Strong acids, glass
10.6 Hazardous decomposition products
Hazardous decomposition products formed under fire conditions. - Hydrogen fluoride, Lithium oxides
Other decomposition products - No data available
In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects
Acute toxicity
No data available
Inhalation: No data available
Dermal: No data available
No data available
Skin corrosion/irritation
No data available
Serious eye damage/eye irritation
No data available
Respiratory or skin sensitisation
No data available
Germ cell mutagenicity
No data available
Carcinogenicity
IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Lithium-6 fluoride)
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity
Effects on or via lactation
Suspected human reproductive toxicant
No data available
Specific target organ toxicity - single exposure
No data available
Specific target organ toxicity - repeated exposure
No data available
Aspiration hazard
No data available
Additional Information
RTECS: Not available
Fluoride ion can reduce serum calcium levels possibly causing fatal hypocalcemia.
Large doses of lithium ion have caused dizziness and prostration, and can cause kidney damage if sodium intake is limited. Dehydration, weight loss, dermatological effects, and thyroid disturbances have been reported.
Central nervous system effects that include slurred speech, blurred vision, sensory loss, ataxia, and convulsions may occur. Diarrhea, vomiting, and neuromuscular effects such as tremor, clonus, and hyperactive reflexes may occur as a result of repeated exposure to lithium ion., Salivation, Nausea, Abdominal pain, Vomiting, Fever, Rapid respiration, Fluoride ion can reduce serum calcium levels possibly causing fatal hypocalcemia., burning sensation, Cough, wheezing, laryngitis, Shortness of breath
Stomach - Irregularities - Based on Human Evidence
Stomach - Irregularities - Based on Human Evidence

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity
No data available
12.2 Persistence and degradability
No data available
12.3 Bioaccumulative potential
No data available
12.4 Mobility in soil
No data available
12.5 Results of PBT and vPvB assessment
PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
12.6 Other adverse effects
No data available

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods
Product
Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent

and burn in a
chemical incinerator equipped with an afterburner and scrubber.
Contaminated packaging
Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

UN number: 3288 Class: 6.1 Packing group: III

Proper shipping name: Toxic solid, inorganic, n.o.s. (Lithium-6 fluoride)

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 3288 Class: 6.1 Packing group: III EMS-No: F-A, S-A

Proper shipping name: TOXIC SOLID, INORGANIC, N.O.S. (Lithium-6 fluoride)

IATA

UN number: 3288 Class: 6.1 Packing group: III

Proper shipping name: Toxic solid, inorganic, n.o.s. (Lithium-6 fluoride)

SECTION 15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De

Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

Lithium-6 fluoride

CAS-No.

14885-65-5

Revision Date

2008-06-01

New Jersey Right To Know Components

Lithium-6 fluoride

CAS-No.

14885-65-5

Revision Date

2008-06-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.